



Juniper EX2300 Series Ethernet Switches Datasheet



Router-Switch.com
Leading Network Hardware Supplier

CONTENT

Content.....	1
overview.....	2
Product Description.....	2
Appearance.....	4
Features and Benefits.....	5
Specifications.....	7
Ordering information.....	18
Where to Buy.....	21
Sources.....	21

Contact Us

Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166 /

Fax: +852-3050-1066 (Hong Kong)

Email: sales@router-switch.com (Sales Inquiries)

OVERVIEW

The Juniper Networks EX2300 Ethernet Switch offers an economical, entry-level, standalone solution for access-layer deployments in branch and remote offices, as well as enterprise campus networks. Both 1 Gbps and 2.5 Gbps access port options are available to provide higher-speed options, especially when connecting to 802.11ac Wave 2 access points.

For small networks, up to four EX2300 switches can be interconnected in a Virtual Chassis configuration, allowing them to be managed as a single switch.

PRODUCT DESCRIPTION

The Juniper Networks® EX2300 line of Ethernet switches offers a compact, high-performance solution for supporting today's converged network access deployments.

Each EX2300 switch includes an ASIC-based Packet Forwarding Engine (PFE) with an integrated CPU to consistently deliver wire-rate forwarding, even with all control plane features enabled. Based on existing, field-proven Juniper Networks technology, the PFE brings the same level of carrier-class performance and reliability to the EX2300 switches that Juniper Networks routers bring to the world's largest service provider networks.

Select EX2300 models also support the 802.3af Class 3 Power over Ethernet (PoE) and 802.3at PoE+ standards for supporting networked devices such as telephones, video cameras, IEEE 802.11ac WLAN access points, and videophones in converged networks. The PoE-enabled EX2300 switches include a maximum system budget of 750 watts to deliver up to 30 watts to select ports.

Multiple EX2300 models are available, including versions offering multigigabit (up to 2.5 Gbps) PoE+ access ports that can accommodate higher-speed IEEE 802.11ac Wave 2 access points, enabling the switches to support more wireless users.

The EX2300 fixed-configuration Ethernet switches provide exceptional value to enterprise customers by supporting the following key technologies:

- Virtual Chassis technology enables up to four interconnected EX2300 switches to form a single logical device.
- Flexible 1GbE SFP/10GbE SFP+ uplinks provide high-speed connectivity to aggregation layer switches or other upstream devices.
- Up to 48 10/100/1000BASE-T ports are available with or without PoE/PoE+.

- Models offering 24 and 48 multigigabit ports support 1GbE/2.5GbE on 8 and 16 ports, respectively
- Energy Efficient Ethernet (EEE) support is provided on 1GbE ports.
- Complete Layer 2 and basic Layer 3 switching capabilities are available.
- Simplified management uses Juniper Networks Junos Space Network Director and J-Web GUI.

Additional features include:

- PoE-enabled EX2300 switches can simultaneously deliver up to 15.4 watts of standards-based 802.3af Class 3 PoE to a maximum of 48 ports or 30 watts of standards-based 802.3at PoE+ to a maximum of 24 ports, based on a total system budget of 750 watts.
- Uplink ports can be configured as Virtual Chassis interfaces and connected via standard 10GbE optics interfaces (optional Virtual Chassis license required).
- Fixed power supply and uplink ports ensure operational simplicity.
- Low power consumption, low acoustic fans, and a small 10-inch deep footprint enable flexible, environmentally friendly deployment.
- Support for L2 protocols as well as L3 protocols like RIP and static routing are included in the base license.
- Support is available for IPv6 management, including neighbor discovery, telnet, SSH, DNS, system log, and NTP.
- A single release train for Juniper Networks Junos operating system is supported to ensure a consistent control plane feature implementation.
- Modular Junos OS prevents a switch reboot if a single protocol feature fails.
- Built-in Web interface (Juniper Networks J-Web Software) is provided.
- RJ-45 serial console port is available.
- USB mini console port is included on 1GbE access switch models.
- Out-of-band Ethernet management port is provided.
- Reduction of Hazardous Waste (RoHS) is certified.

APPEARANCE

Figure 1. Juniper EX2300-24T/24P



Figure 2. Juniper EX2300-48T/48P



Figure 3. Juniper EX2300-24MP



Figure 4. Juniper EX2300-48MP



High Availability Features

To avoid the complexities of the Spanning Tree Protocol (STP) without sacrificing network resiliency, the EX2300 employs a redundant trunk group (RTG) to provide the necessary port redundancy and simplify switch configuration. It also supports cross-member link aggregation, which allows redundant link aggregation connections between devices in a single Virtual Chassis configuration, providing an additional level of reliability and availability.

Junos Operating System

The EX2300 switches run the same Junos OS that is used by other Juniper Networks EX Series Ethernet Switches, QFX Series Switches, Juniper Routers, Juniper SRX Firewalls, and the Juniper NFX Series Network Services Platform. By utilizing a common operating system, Juniper delivers a consistent implementation and operation of control plane features across all products. To maintain that consistency, the Junos OS adheres to a highly disciplined development process that uses a single source code, and it employs a highly available modular architecture that prevents isolated failures from bringing down an entire system.

These attributes are fundamental to the core value of the software, enabling all Junos OS-powered products to be updated simultaneously with the same software release. All features are fully regression-tested, making each new release a true superset of the previous version. Customers can deploy the software with complete confidence that all existing capabilities are maintained and operate in the same way.

Converged Environments

The EX2300 provides the highest levels of flexibility and features in its class for the most demanding converged data, voice, and video environments, delivering a reliable platform for unifying enterprise communications.

By providing a full 15.4 watts of Class 3 PoE to VoIP telephones, closed-circuit security cameras, wireless access points, and other IP-enabled devices, the EX2300 delivers a future-proofed solution for converging disparate networks onto a single IP infrastructure. The EX2300 PoE switches also support 802.3at standards-based PoE+, delivering 30 watts for powering networked devices such as IEEE 802.11ac wireless access points, and videophones that might require more power than available with IEEE 802.3af.

To ease deployment, the EX2300 supports the industry standard Link Layer Discovery Protocol (LLDP) and LLDP Media Endpoint Discovery (LLDP-MED) protocol, enabling the switches to automatically discover Ethernet-enabled devices, determine their power requirements, and assign virtual LAN (VLAN) membership. LLDP-MED-based granular PoE management allows the EX2300 to negotiate PoE usage down to a fraction of a watt on powered devices, enabling more efficient PoE utilization across the switch.

In addition, the EX2300 supports rich quality-of-service (QoS) functionality for prioritizing data, voice, and video traffic. The switches support eight class-of-service (CoS) queues on every port, enabling them to maintain multilevel, end-to-end traffic prioritizations. The EX2300 also supports a wide range of policy options, including strict priority, low latency, weighted random early detection (WRED), and shaped-deficit weighted roundrobin (SDWRR) queuing.

Security

Working as an enforcement point in Access Policy Infrastructure, the EX2300 provides both standards-based 802.1X port level access control for multiple devices per port, as well as Layer 2-4 policy enforcement based on user identity, location, device, or a combination of these. A user's identity, device type, machine posture check, and location can be used to determine whether access should be granted and for how long. If access is granted, the switch provides access to the network based on authorization attributes sent by the authentication server. The switch can also apply security policies, QoS policies, or both, or it can mirror user traffic to a central location for logging, monitoring, or threat detection by intrusion prevention systems.

The EX2300 also provides a full complement of integrated port security and threat detection features, including Dynamic Host Configuration Protocol (DHCP) snooping, dynamic ARP inspection (DAI), and media access control (MAC) limiting to defend against internal and external spoofing, and man-in-the-middle and denial of service (DoS) attacks.

Junos Space

Juniper also offers a comprehensive suite of network management tools that provide a smart, simple, and open approach for automating the deployment and operation of a Juniper infrastructure.

These tools are based on a single network application platform called Juniper Networks Junos Space, an open, programmable application platform for hosting network infrastructure and operational applications across the entire management life cycle of the network. Explicitly designed to allow partners and customers to build and deploy smart, simple, and easy-to-use applications, Junos Space provides multiple management and infrastructure applications for managing Juniper resources and

assets, including inventory management, device and interface configuration, automated software management and deployment, and event-driven fault management. These platform applications are embedded within the core product, allowing users to control any part of their environment when used in conjunction with multiple add-on applications. Junos Space supports a full portfolio of applications for automating network infrastructure and operations covering the campus LAN and data center network environments.

Designed to automate the configuration, visualization, monitoring, and administration of large switch and router networks, these Junos Space applications offer predefined automation schemes and best practice templates to enable rapid and accurate deployments. When managing a group of EX2300 switches, the Junos Space platform and associated applications provide network-level management across all Juniper Networks switches from a single console.

Network Director can manage the EX2300 as a standalone switch.

Juniper Sky Enterprise

The EX2300 line is supported by Juniper Sky Enterprise, a cloud management solution that provides a 'phone home' capability for branch devices, eliminating pre-staging and allowing the platforms to be managed from a central location. The simple yet flexible Juniper Sky Enterprise solution also supports all other EX Series switches as well as standard SRX Series Services Gateways, allowing customization at the operations center.

Enhanced Limited Lifetime Warranty

The EX2300 includes an enhanced limited lifetime hardware warranty that provides return-to-factory switch replacement for as long as the original purchaser owns the product. The warranty includes lifetime software updates, advanced shipping of spares within one business day, and 24x7 Juniper Networks Technical Assistance Center (JTAC) support for 90 days after the purchase date. Power supplies and fan trays are covered for a period of five years.

SPECIFICATIONS

Table 1. Power Options of Juniper EX2300 Switches

Model	Max. System Power Consumption without PoE	(Input Power)	Power	Total PoE Power Budget

EX2300-24T	55 W AC	0
EX2300-24P	80 W AC	370 W
EX2300-24MP	55 W AC	380 W
EX2300-48T	70 W AC	0
EX2300-48P	100 W AC	750 W
EX2300-48MP	90 W AC	750 W

Table 2. Physical Specifications of Juniper EX2300 Switches

Physical Specifications	
Dimensions (W x H x D)	<ul style="list-style-type: none"> ● Width: <ul style="list-style-type: none"> - 17.4 in (44.19 cm) for desktop installations - 17.5 in (44.6 cm) with rack-mount brackets Height: 1.75 in (4.45 cm) for 1U installations ● Depth: <ul style="list-style-type: none"> - EX2300-24T: 10.2 in (25.9 cm) - EX2300-24P: 12.2 in (30.98 cm) - EX2300-24MP: 10 in (25.4 cm) - EX2300-48T: 10.2 in (25.9 cm) - EX2300-48P: 12.2 in (30.98 cm) - EX2300-48MP: 14.5 in (36.83 cm)
Backplane	<ul style="list-style-type: none"> ● 80 Gbps Virtual Chassis interconnect to link up to four switches as a single logical device (EX2300-24/48T/P and EX2300-24/48 MP models)

System Weight	<ul style="list-style-type: none"> ● EX2300-24T: 7.25 lb (3.29 kg) ● EX2300-24P: 9.89 lb (4.49 kg) ● EX2300-24MP: 8.82 lb (4 kg) ● EX2300-48T: 8.29 lb (3.76 kg) ● EX2300-48P: 11.07 lb (5.02 kg) ● EX2300-48MP: 14.33 lb (6.5 kg)
Environmental Ranges	<ul style="list-style-type: none"> ● Operating temperature: 32° to 113° F (0° to 45° C) ● Storage temperature: -40° to 158° F (-40° to 70° C) ● Operating altitude: up to 13,000 ft (3962 m) at 40° C according to GR-63 ● Non-operating altitude: up to 15,000 ft (4572 m) ● Relative humidity operating: 10% to 85% (noncondensing) <p>Relative humidity non-operating: 0% to 95% (noncondensing)</p>
Cooling	<ul style="list-style-type: none"> ● Airflow: <ul style="list-style-type: none"> - EX2300-24T: 25 cfm - EX2300-24P: 23 cfm - EX2300-48T: 24 cfm - EX2300-48P: 25 cfm
Hardware Specifications	
Switching Engine Model	<ul style="list-style-type: none"> ● Store and forward
DRAM	<ul style="list-style-type: none"> ● 2 GB (EX2300-24/48T/P)
Flash	<ul style="list-style-type: none"> ● 2 GB (EX2300 non-multigigabit models) ● 8 GB (EX2300-24MP, EX2300-48MP)
CPU	<ul style="list-style-type: none"> ● 1.25GHz ARM CPU
GbE Port Density per System	<ul style="list-style-type: none"> ● EX2300-24P/24T/24MP: 28 (24 host ports + four-port SFP/SFP+ uplinks) ● EX2300-48P/48T: 52 (48 host ports + four-port SFP/SFP+ uplinks) ● EX2300-48MP: 54 (48 host ports + six-port SFP/SFP+ uplinks)
Supported Optics	<ul style="list-style-type: none"> ● 10/100/1000BASE-T connector type RJ-45 ● GbE SFP optic/connector type: RJ-45, or LC SFP fiber supporting 1000BASE-T SFP, SX (multimode), LX (singlemode), or LH (single-mode)
Physical Layer	<ul style="list-style-type: none"> ● Physical port redundancy: Redundant trunk group (RTG)

	<ul style="list-style-type: none"> ● Cable diagnostics for detecting cable breaks and shorts ● Auto MDI/MDIX (medium-dependent interface/mediumdependent interface crossover) support ● Port speed downshift/setting maximum advertised speed on 10/100/1000BASE-T ports ● Digital optical monitoring for optical ports
Packet-Switching Capacities (Maximum with 64-Byte Packets)	<ul style="list-style-type: none"> ● EX2300-24P/24T: 64 Gbps (unidirectional)/128 Gbps (bidirectional) ● EX2300-24MP: 76 Gbps (unidirectional)/ 152 Gbps (bidirectional) ● ● EX2300-48P/48T: 88 Gbps (unidirectional)/176 Gbps (bidirectional) ● EX2300-48MP: 132 Gbps (unidirectional)/264 Gbps (bidirectional)
Software Specifications	
Layer 2/Layer 3 Throughput (Mpps) (Maximum with 64 Byte Packets)	<ul style="list-style-type: none"> ● EX2300-24P/24T/24MP: 95 Mpps (wire speed) ● EX2300-48P/48T/48MP: 130 Mpps (wire speed)
Layer 2 Features	<ul style="list-style-type: none"> ● Maximum MAC addresses in hardware: 16,000 ● Jumbo frames: 9216 bytes ● Number of VLANs supported: 4093 (2044 active VLAN) ● Range of possible VLAN IDs: 1-4094 ● Port-based VLAN ● MAC-based VLAN ● Voice VLAN ● Layer 2 Protocol Tunneling (L2PT) ● IEEE 802.1ak: Multiple VLAN Registration Protocol (MVRP) ● Compatible with Per-VLAN Spanning Tree Plus (PVST+) ● RVI (Routed VLAN Interface) ● IEEE 802.1AB: Link Layer Discovery Protocol (LLDP) ● LLDP-MED with VoIP integration ● IEEE 802.1ad Q-in-Q tunneling ● IEEE 802.1br: Bridge Port Extension ● IEEE 802.1D: Spanning Tree Protocol ● IEEE 802.1p: CoS Prioritization

	<ul style="list-style-type: none"> ● IEEE 802.1Q: VLAN Tagging ● IEEE 802.1Q-in-Q: VLAN Stacking ● IEEE 802.1s: Multiple Spanning Tree Protocol (MSTP) ● Number of MST instances supported: 64 ● Number of VSTP instances supported: 253 ● IEEE 802.1w: Rapid Spanning Tree Protocol (RSTP) ● IEEE 802.1X: Port Access Control ● IEEE 802.3: 10BASE-T ● IEEE 802.3u: 100BASE-T ● IEEE 802.3ab: 1000BASE-T ● IEEE 802.3z: 1000BASE-X ● IEEE 802.3af: PoE ● IEEE 802.3at: PoE+ ● IEEE 802.3ad: Link Aggregation Control Protocol (LACP) ● IEEE 802.3x: Pause Frames/Flow Control ● IEEE 802.3az: Energy Efficient Ethernet
Layer 3 Features: IPv4	<ul style="list-style-type: none"> ● Maximum number of ARP entries: 1,500 ● Maximum number of IPv4 unicast routes in hardware: 512 prefixes; 4,096 host routes ● Maximum number of IPv4 multicast routes in hardware: 2,048 groups; 2,048 multicast routes ● Routing Protocols: RIP v1/v2, OSPF v1/v2 ● Static routing ● Routing policy ● Bidirectional Forwarding Detection (BFD) with slow timers (> 3 sec) ● IP directed broadcast
Layer 3 Features: IPv6	<ul style="list-style-type: none"> ● Maximum number of Neighbor Discovery (ND) entries: 1,500 ● Maximum number of IPv6 unicast routes in hardware: 512 prefixes; 2,048 host routes ● Maximum number of IPv6 multicast routes in hardware: 1,024 groups; 1,024 multicast routes ● Neighbor discovery, system logging, Telnet, SSH, SNMP, Network Time

	<p>Protocol (NTP), Domain Name System (DNS)</p> <ul style="list-style-type: none"> • Static routing • Routing protocols: RIPng, OSPF v3, Multicast Listener Discovery, Multicast Listener Discovery v2
Access Control Lists (ACLs) (Junos OS Firewall Filters)	<ul style="list-style-type: none"> • Port-based ACL (PACL)—256 ingress; 256 egress • VLAN-based ACL (VACL)— 256 ingress; 256 egress • Router-based ACL (RACL)—256 ingress; 512 egress • ACL entries (ACE) in hardware per system: 2,000 • ACL counter for denied packets • ACL counter for permitted packets • Ability to add/remove/change ACL entries in middle of list (ACL editing) • L2-L4 ACL
Access Security	<ul style="list-style-type: none"> • MAC limiting • Allowed MAC addresses—configurable per port • Sticky MAC (persistent MAC address learning) • Dynamic ARP inspection (DAI) • Proxy ARP • Static ARP support • DHCP snooping • 802.1X port-based • 802.1X multiple supplicants • 802.1X with VLAN assignment • 802.1X with authentication bypass access (based on host MAC address) • 802.1X with VoIP VLAN support • 802.1X dynamic ACL based on RADIUS attributes • 802.1X Supported EAP types: Message Digest 5 (MD5), Transport Layer Security (TLS), Tunneled Transport Layer Security (TTLS), Protected Extensible Authentication Protocol (PEAP) • IPv6 RA Guard • IPv6 Neighbor Discovery Inspection • Captive Portal

	<ul style="list-style-type: none"> ● Static MAC authentication ● MAC-RADIUS ● Control plane DoS protection ● Fallback authentication ● Trusted Network Connect (TNC) certified
High Availability	<ul style="list-style-type: none"> ● Link aggregation ● 802.3ad (LACP) support: <ul style="list-style-type: none"> - Number of LAGs supported: 128 - Maximum number of ports per LAG: 8 ● Tagged ports support in LAG ● Uplink Failure Detection
Quality of Service (QoS)	<ul style="list-style-type: none"> ● Layer 2 QoS ● Layer 3 QoS ● Ingress policing: one-rate two-color; two-rate three-color markers ● Hardware queues per port: 8 ● Scheduling methods (egress): Strict Priority (SP), shaped deficit weighted round-robin (SDWRR) ● 802.1p, DSCP /IP precedence trust and marking ● L2-L4 classification criteria: Interface, MAC address, EtherType, 802.1p, VLAN, IP address, DSCP/IP precedence, TCP/UDP port numbers ● Congestion avoidance capabilities: Tail drop and WRED
Multicast	<ul style="list-style-type: none"> ● IGMP snooping entries: 2,000 ● IGMP: v1, v2, v3 ● IGMP snooping ● PIM-SM, PIM-SSM, PIM-DM ● MLD snooping
Services and Manageability	<ul style="list-style-type: none"> ● Junos OS CLI ● Web interface (J-Web) ● Out-of-band management: Serial, 10/100BASE-T Ethernet ● ASCII configuration ● Rescue configuration

	<ul style="list-style-type: none"> ● Configuration rollback ● Image rollback ● Element management tools: Junos Space Network Management Platform ● Simple Network Management Protocol (SNMP): v1, v2c, v3 ● Remote monitoring (RMON) (RFC 2819) Groups 1, 2, 3, 9 ● Network Time Protocol (NTP) ● DHCP server ● DHCP client and DHCP proxy ● DHCP relay and helper ● RADIUS authentication ● TACACS+ authentication ● SSHv2 ● Secure copy ● HTTP/HTTPs ● DNS resolver ● System log logging ● Temperature sensor ● Configuration backup via FTP/secure copy ● Interface range
Supported RFCs	<ul style="list-style-type: none"> ● RFC 768 UDP ● RFC 783 Trivial File Transfer Protocol (TFTP) ● RFC 791 IP ● RFC 792 Internet Control Message Protocol (ICMP) ● RFC 793 TCP ● RFC 826 ARP ● RFC 854 Telnet client and server ● RFC 894 IP over Ethernet ● RFC 903 Reverse ARP (RARP) ● RFC 906 Bootstrap Loading using TFTP ● RFC 951, 1542 BootP

	<ul style="list-style-type: none"> ● RFC 1027 Proxy ARP ● RFC 1058 RIP v1 ● RFC 1122 Requirements for Internet Hosts ● RFC 1256 IPv4 ICMP Router Discovery (IRDP) ● RFC 1492 TACACS+ ● RFC 1519 Classless Interdomain Routing (CIDR) ● RFC 1591 Domain Name System (DNS) ● RFC 1812 Requirements for IP Version 4 routers ● RFC 2030 Simple Network Time Protocol (SNTP) ● RFC 2068 HTTP/1.1 ● RFC 2131 BOOTP/DHCP relay agent and DHCP server ● RFC 2138 RADIUS Authentication ● RFC 2139 RADIUS Accounting ● RFC 2267 Network Ingress Filtering ● RFC 2453 RIP v2 ● RFC 2474 DiffServ Precedence, including 8 queues/port ● RFC 2597 DiffServ Assured Forwarding (AF) ● RFC 2598 DiffServ Expedited Forwarding (EF) ● RFC 2710 Multicast Listener Discovery Version (MLD) for IPv6 ● RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations ● RFC 3176 sFlow ● RFC 3579 RADIUS Extensible Authentication Protocol (EAP) support for 802.1X ● RFC 5176 Dynamic Authorization Extensions to RADIUS ● LLDP Media Endpoint Discovery (LLDP-MED), ANSI/TIA1057, draft 08
Supported MIBs	<ul style="list-style-type: none"> ● RFC 1155 Structure of Management Information (SMI) ● RFC 1157 SNMPv1 ● RFC 1212, RFC 1213, RFC 1215 MIB-II, Ethernet-like MIB, and TRAPs ● RFC 1493 Bridge MIB ● RFC 1643 Ethernet MIB

- RFC 1724 RIPv2 MIB
- RFC 1905 RFC 1907 SNMP v2c, SMIPv2 and Revised MIB-II
- RFC 1981 Path MTU Discovery for IPv6
- RFC 2011 SNMPv2 Management Information Base for the IP using SMIPv2
- RFC 2012 SNMPv2 Management Information Base for the Transmission Control Protocol using SMIPv2
- RFC 2013 SNMPv2 Management Information Base for the User Datagram Protocol using SMIPv2
- RFC 2096 IPv4 Forwarding Table MIB
- RFC 2287 System Application Packages MIB
- RFC 2460 IPv6 Specification
- RFC 2464 Transmission of IPv6 Packets over Ethernet Networks
- RFC 2570-2575 SNMPv3, User-based Security, Encryption, and Authentication
- RFC 2576 Coexistence between Version 1, Version 2, and Version 3 of the Internet-standard Network Management Framework
- RFC 2578 SNMP Structure of Management Information MIB
- RFC 2579 SNMP Textual Conventions for SMIPv2
- RFC 2665 Definitions of Managed Objects for the Ethernet-like Interface Types
- RFC 2819 RMON MIB
- RFC 2863 The Interfaces Group MIB
- RFC 2922 LLDP MIB
- RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations
- RFC 3413 SNMP Application MIB
- RFC 3414 User-based Security Model for SNMPv3
- RFC 3415 View-based Access Control Model (VACM) for SNMP
- RFC 3484 Default Address Selection for IPv6
- RFC 3621 PoE-MIB (PoE switches only)
- RFC 3810 Multicast Listener Discovery Version 2 (MLDv2) for IPv6
- RFC 4188 STP and Extensions MIB

	<ul style="list-style-type: none"> ● RFC 4213 Basic Transition Mechanisms for IPv6 Hosts and Routers ● RFC 4291 IPv6 Addressing Architecture ● RFC 4363 Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering, and VLAN Extensions ● RFC 4443 ICMPv6 for the IPv6 Specification ● RFC 4861 Neighbor Discovery for IPv6 ● RFC 4862 IPv6 Stateless Address Autoconfiguration ● Draft - blumenthal - aes - usm - 08 ● Draft - reeder - snmpv3 - usm - 3desede -00
Troubleshooting	<ul style="list-style-type: none"> ● Debugging: CLI via console, telnet, or SSH ● Diagnostics: Show and debug command statistics ● Traffic mirroring (port) ● Traffic mirroring (VLAN) ● ACL-based mirroring ● Mirroring destination ports per system: 4 ● LAG port monitoring ● Multiple destination ports monitored to 1 mirror (N:1) ● Maximum number of mirroring sessions: 4 ● Mirroring to remote destination (over L2): 1 destination VLAN ● Encapsulated Remote Switched Port Analyzer (ERSPAN) ● IP tools: Extended ping and trace ● Juniper Networks commit and rollback
Safety Certifications	<ul style="list-style-type: none"> ● UL-UL60950-1 (Second Edition) ● C-UL to CAN/CSA 22.2 No.60950-1 (Second Edition) ● TUV/GS to EN 60950-1 (Second Edition) ● CB-IEC60950-1 (Second Edition with all country deviations) ● EN 60825-1 (Second Edition)
Electromagnetic Compatibility Certifications	<ul style="list-style-type: none"> ● FCC 47CFR Part 15 Class A ● EN 55022 Class A ● ICES-003 Class A ● VCCI Class A

	<ul style="list-style-type: none"> ● AS/NZS CISPR 22 Class A ● CISPR 22 Class A ● EN 55024 ● EN 300386 ● CE
Telecom Quality Management	<ul style="list-style-type: none"> ● TL9000
Environmental	<ul style="list-style-type: none"> ● Reduction of Hazardous Substances (ROHS) 6
Telco	<ul style="list-style-type: none"> ● CLEI code

Noise Specifications

Noise measurements based on operational tests taken from bystander position (front) and performed at 25° C in compliance with ISO 7779. The PoE load was 370 W (24 ports powered at 15.4W each) on the EX2300-24P and 740 W (48 ports powered at 15.4W each) on the EX2300-48P.

Table 3. Noise Specifications of Juniper EX2300 Switches.

Model	Acoustic Noise in DB
EX2300-24T	34.2
EX2300-24P	40.6
EX2300-48T	34.6
EX2300-48P	51.4
EX2300-24MP	45.7
EX2300-48MP	45.8

ORDERING INFORMATION

Table 4. Ordering information

Product number	Product description
Switches	

EX2300-24T	EX2300 24-port 10/100/1000BASE-T, 4 x 1/10GbE SFP/SFP+ (optics sold separately)
EX2300-24T-VC	EX2300 24-port non-PoE+ w/ Virtual Chassis License
EX2300-24P	EX2300 24-port 10/100/1000BASE-T PoE+, 4 x 1/10GbE SFP/SFP+ (optics sold separately)
EX2300-24P-VC	EX2300 24-port PoE+ w/ Virtual Chassis License
EX2300-24MP	EX2300 16-port 10/100/1000BASE-T PoE+, 8-port 10/100/1000/2500BASE-T PoE+, 4 x 1/10GbE SFP/ SFP+ (optics sold separately)
EX2300-24T-DC	EX2300 24-port 10/100/1000BASE-T with internal DC PSU, 4 x 1/10GbE SFP/SFP+ (optics sold separately)
EX2300-24T-TAA	EX2300 TAA 24-port 10/100/1000BASE-T, 4 x 1/10GbE SFP/SFP+ (optics sold separately)
EX2300-24P-TAA	EX2300 TAA 24-port 10/100/1000BASE-T PoE+, 4 x 1/10GbE SFP/SFP+ (optics sold separately)
EX2300-48T	EX2300 48-port 10/100/1000BASE-T, 4 x 1/10GbE SFP/SFP+ (optics sold separately)
EX2300-48T-VC	EX2300 48-port non-PoE+ w/ Virtual Chassis License
EX2300-48P	EX2300 48-port 10/100/1000BASE-T PoE+, 4 x 1/10GbE SFP/SFP+ (optics sold separately)
EX2300-48P-VC	EX2300 48-port PoE+ w/ Virtual Chassis License
EX2300-48MP	EX2300 32-port 10/100/1000BASE-T PoE+, 16-port 10/100/1000/2500BASE-T PoE+, 6 x 1/10GbE SFP/ SFP+ (optics sold separately)

EX2300-48T-TAA	EX2300 TAA 48-port 10/100/1000BASE-T, 4 x 1/10GbE SFP/SFP+ (optics sold separately)
EX2300-48P-TAA	EX2300 TAA 48-port 10/100/1000BASE-T PoE+, 4 x 1/10GbE SFP/SFP+ (optics sold separately)

WHERE TO BUY

Want to buy this series of products? please contact:

- Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com (Sales Inquiries)

Or visit: [Juniper EX2300 Series Ethernet Switches](#)

About us

Router-switch.com (HongKong Yejian Technologies Co., Ltd), founded in 2002, is one of the biggest Global Network Hardware Supplier. We are a leading provider of network products with 18,000+ customers in over 200 countries. We provide original new and used network equipments ([Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Juniper](#), EMC, etc.), including Routers, Switches, Servers, Storage, Telepresence and Videoconferencing, IP Phones, Firewalls, Wireless APs & Controllers, EHWIC/HWIC/VWIC Cards, SFPs, Memory & Flash, Hard Disk, Cables, and all kinds of network solutions related products.

SOURCES

<https://www.juniper.net/us/en/products-services/switching/ex-series/datasheets/1000579.page>